



The Fully-automatic Era of iCa²⁺ Solution





Equipped with Puncture Pipettor, No Need to Decap Before Test

- The maximum anaerobic environment ensures the stability of ionized calcium levels and the accuracy of measurement
- Avoiding the biological hazards caused by decapping to protect the clinical workers



Connectable to Total Laboratory Automation System

• Fit customized needs from small labs to large labs

Fully Automatic Sample Loading and Information Reading

- Up to 90 samples per hour (540 tests per hour)
- 30 samples can be loaded in a single operation, supporting continuous loading
- Barcode scanner to automatically read sample information

User-centric Design

- 12-inch color LCD touch screen, concise and intuitive design
- Drag-out ISE module and portable electrode replacement ensure convenient maintenance

Basic information	
Test method	Ion selective electrodes (direct)
Sample type	Whole blood, serum, urine
Sampling volume	100 μL
Liquid level detection	Capacitive liquid level detection
Software platform	Android
Configuration	
Electrodes	6 electrodes as per request of any combination
Extendibility	
LIS	Support LIS connection
Result printing	Built-in thermal printer/Support connecting to external printer
Interface	2 USB, 1 COM, 1 LAN
Program upgrade	Support online program upgrade
Visualization	
Data statistics and instrument status monitoring	Slope tracking chart, L-J quality control chart, X-barM (floating mean quality control) chart

* Specifications may be modified without notice. Please inquire Snibe representative for updates.

Biossays® is a trademark of Snibe. All other product names and trademarks are the property of their respective owners.



Shenzhen New Industries Biomedical Engineering Co., Ltd. No.23, Jinxiu East Road, Pingshan District, 518122 Shenzhen, P.R. China

 Tel: +86 755 26501514
 Fax: +86 755 26654850

 Email: sales@snibe.com
 Web: www.snibe.com

Follow us on

